

## Matric System 25: Midpin 40 C6



**DE** Midpin LED-Strahler für modulares Matric 48V-Stromschienensystem. 350° drehbar und 90° schwenkbar. Gehäuse aus Aluminium in unterschiedlichen Lackierungen und Kombinationen erhältlich, z.B. weiß, silber, graphit, schwarz, gold oder kupferfarben lackiert. Weitere Oberflächenoptionen siehe Lightnet Surface Collection oder RAL nach Wahl. Adapter und Gelenk immer schwarz. Farbtemperatur wahlweise 2700K, 3000K oder 4000K oder als Dim to Warm 3000K-1800K. Farbwiedergabe CRI>90. Binning initial  $\leq$  MacAdam 3. Spezielle mehrstufige Optiklinsen für Konturbeleuchtung. Optikring in verschiedenen Farbausführungen erhältlich. Wahlweise einfach schaltbar oder stufenlos dimmbar (DALI).

**EN** Midpin LED spotlight for modular Matric 48V track system. 350° rotation and 90° tilt. Aluminium housing available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For further surface options see Lightnet-Surface-Collection or RAL of your choice. Adapter and joint always black. Colour temperature available as 2700K, 3000K or 4000K or as Dim to Warm 3000K-1800K. Colour rendering CRI>90. Binning  $\leq$  MacAdam 3. Special multi-stage optical lenses for contour lighting. Optic ring available in different colour versions. Optionally switchable or dimmable (DALI)..

**D C6 9 WE - 9 27M**

|                    |                                                                                                                                                                                                                                                                                                                      |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Family     | <b>D:</b> Midpin                                                                                                                                                                                                                                                                                                     |
| Type               | <b>C6:</b> Spotlight Camera Ø40mm                                                                                                                                                                                                                                                                                    |
| Optical System     | <b>9:</b> Contour Frame Lens 24°- 32°                                                                                                                                                                                                                                                                                |
| Surface Finish     | <b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>F:</b> Anodic Silver, <b>U:</b> Urban Graphite, <b>D:</b> Anodic Black, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne, <b>K:</b> Satin Copper, <b>X:</b> Satin Bronze, <b>M:</b> Satin Cloud, <b>R:</b> Special Surface (please specify) |
| Control Gear       | <b>E:</b> On/Off, <b>L:</b> DALI                                                                                                                                                                                                                                                                                     |
| Colour Rendering   | <b>9:</b> CRI>90                                                                                                                                                                                                                                                                                                     |
| Colour Temperature | <b>27:</b> 2700K, <b>30:</b> 3000K, <b>40:</b> 4000K, <b>DW:</b> Dim to Warm 3000K-1800K [DALI only]                                                                                                                                                                                                                 |
| Power              | <b>E:</b> Low Power, <b>M:</b> Medium Power                                                                                                                                                                                                                                                                          |

