

LUCE SOFT

round



LUCE SOFT Q

square



MAX 3 SOFT



Faretto da incasso a led di forma rotonda; grazie al design lineare e alla cura della forma estetica questo prodotto oltre che essere utilizzato per l'illuminazione d'accento risulta un elemento decorativo nell'ambiente in cui viene applicato. Corpo in alluminio anodizzato, completo di molle per il fissaggio. Copertura decorativa in materiale plastico con effetto opacizzante.

Recessed led spotlight for decorative lighting. Body in anodized aluminium, complete with fixing clips or O-ring. Protection degree is IP65. This spot light comes with a frosted cover in a round or squared shape.

Faretto da incasso a led di forma quadrata; grazie al design lineare e alla cura della forma estetica questo prodotto oltre che essere utilizzato per l'illuminazione d'accento risulta un elemento decorativo nell'ambiente in cui viene applicato. Corpo in alluminio anodizzato, completo di molle per il fissaggio. Copertura decorativa in materiale plastico con effetto opacizzante.

Recessed led spotlight for decorative lighting. Body in anodized aluminium, complete with fixing clips or O-ring. Protection degree is IP65. This spot light comes with a frosted cover in a round or squared shape.

Apparecchio decorativo da incasso a led per applicazione da interno o esterno.

Corpo in alluminio anodizzato, diffusore satinato in metacrilato.

Led luminaire for recessed installation, interior and exterior. Body in anodized aluminium. Complete with matt diffuser, vandal resistant. Fixing clips for installation.

LUCE SOFT	EN3005	EN3004
LED Colour	White 3000K or 4000K	
LED Number	1	3
TOTAL Power	2W	3W
Input	500mA	350mA
Weight	0,1 kg	0,1 kg
Lens	-	-
Insulation Class	III	III
IP Code	IP65	IP65
Dimensions	ø 44x66 mm	ø 44x66 mm
Recessed dimension	ø 36 mm	ø 36 mm
Body finishing	AL anodized	AL anodized
Diffuser finishing	Matt elliptical	Matt elliptical

Notes: Drivers not included

LUCE SOFT Q	EN3001	EN3000
LED Colour	White 3000K or 4000K	
LED Number	1	3
TOTAL Power	2W	3W
Input	500mA	350mA
Weight	0,1 kg	0,1 kg
Lens	-	-
Insulation Class	III	III
IP Code	IP65	IP65
Dimensions	44x 44x66 mm	44x44x66 mm
Recessed dimension	ø 36 mm	ø 36 mm
Body finishing	-	AL anodized
Diffuser finishing	Matt square	Matt square

Notes: Drivers not included

MAX 3 SOFT	EN3225
LED Colour	White 3000K or 4000K
LED Number	-
TOTAL Power	4W
Input	230V
Weight	0,3 kg
Lens	15° / 25° / 60°
Insulation Class	I
IP Code	IP65
Dimensions	ø 94x70 mm
Recessed dimensions	ø 70 mm
Body finishing	AL anodized
Diffuser finishing	Cylindrical matt

