

LUCE round



Faretto da incasso a led per illuminazione d'accento. Corpo in alluminio anodizzato o verniciato. Vetro di protezione in materiale plastico trasparente. Ghiera modello tondo leggermente svasato in alluminio anodizzato. Completo di clips di fissaggio.

Led spot lighting fixture for recessed installation, suitable to an intensive lighting effects. Body in anodized aluminium or painted aluminium. Aluminium frame in round shape. Clear protection glass and installation clips.

LUCE Q square



Faretto da incasso a led per illuminazione d'accento. Corpo in alluminio anodizzato o verniciato. Vetro di protezione in materiale plastico trasparente. Ghiera modello quadrato in alluminio anodizzato. Completo di clips di fissaggio.

Led spot lighting fixture for recessed installation, suitable to an intensive lighting effects. Body in anodized aluminium or painted aluminium. Aluminium frame in squared shape. Clear protection glass and installation clips.

LUCE	EN3060	EN3060-10	EN3060-50
LED Colour	White/coloured 3000K or 4000K		
LED Number	1	1	1
TOTAL Power	1,2W - 2W	1,2W - 2W	1,2W - 2W
Input	350mA - 500mA	350mA - 500mA	350mA - 500mA
Weight	0,1 kg	0,1 kg	0,1 kg
Lens	15°/ 25°/ 40°	15°/ 25°/ 40°	15°/ 25°/ 40°
Insulation Class	III	III	III
IP Code	IP67	IP67	IP67
Dimensions	Ø 44x66 mm	Ø 44x66 mm	Ø 44x66 mm
Recessed dimension	Ø 36 mm	Ø 36 mm	Ø 36 mm
Body finishing	AL anodized	White finishing	Stainless Steel
Diffuser finishing	Transparent	Transparent	Transparent

LUCE Q	EN3160	EN3160-10	EN3160-50
LED Colour	White/coloured 3000K or 4000K		
LED Number	1	1	1
TOTAL Power	1,2W - 2W	1,2W - 2W	1,2W - 2W
Input	350mA - 500mA	350mA - 500mA	350mA - 500mA
Weight	0,1 kg	0,1 kg	0,1 kg
Lens	15°/ 25°/ 40°	15°/ 25°/ 40°	15°/ 25°/ 40°
Insulation Class	III	III	III
IP Code	IP67	IP67	IP67
Dimensions	44x44x66 mm	44x44x66 mm	49x49x66 mm
Recessed dimension	Ø 36 mm	Ø 36 mm	Ø 36 mm
Body finishing	AL anodized	White finishing	Stainless Steel
Diffuser finishing	Transparent	Transparent	Transparent

