



TOROLED



Nuovo apparecchio a led per illuminazione di parcheggi, rotonde, grandi aree a piazze. Quattro bracci a 90° da 50 a 300W. Distribuzione fotometrica quadrata al suolo. Installazione su testapalo Ø89mm. Corpo in alluminio estruso, anodizzato colore grigio, attacco a palo in acciaio zincato verniciato bianco RAL9010.

New lighting luminaire with led technology suitable for parks, big areas, squares and public areas in general. It is supplied with four brackets at 90°, 50-300W. Top pole installation Ø89mm. Body in extruded anodized aluminium, grey colour, bracket in galvanized steel painted in white RAL9010.

TOROLED	400	600	800	1000	1200
LED Number	4x48 LEDs	4x72 LEDs	4x96 LEDs	4x120 LEDs	4x144 LEDs
LED Power	2W – 230lm	2W – 230lm	2W – 230lm	2W – 230lm	2W – 230lm
Total Power	400W	600W	800W	1000W	1200W
Optic	Asymmetric lenses	Asymmetric lenses	Asymmetric lenses	Asymmetric lenses	Asymmetric lenses
LED Colour	White 4000K	White 4000K	White 4000K	White 4000K	White 4000K
CRI	>70	>70	>70	>70	>70
Input	230Vac	230Vac	230Vac	230Vac	230Vac
Insulation	Class I-II	Class I-II	Class I-II	Class I-II	Class I-II
IP Rating	IP65	IP65	IP65	IP65	IP65
Dimensions	1450x1450x120mm	1750x1750x120mm	2100x2100x120mm	2200x2200x120mm	2400x2400x120mm
Body	painted steel	painted steel	painted steel	painted steel	painted steel
Diffuser	Clear PMMA	Clear PMMA	Clear PMMA	Clear PMMA	Clear PMMA

Notes: driver included in the luminaire. Dimmable ballast on request. Double bracket-half power version available on request.