

# Midpoint 95 Déco C1 | 3-Phase Track




**DE** LED-Strahler für 3-Phasen-Stromschienen. 350° drehbar und 90° schwenkbar. Rückversetzte sphärische Linse für breitstrahlende Lichtverteilung (70°) und dekorativem konischen Reflektor. Gehäuse-Außenfläche und dekorativer Reflektor in unterschiedlichen Lackierungen und Kombinationen erhältlich, z.B. weiß, silber, graphit, schwarz, gold oder kupferfarben lackiert. Zu Oberflächenoptionen- und Kombinationen siehe Lightnet-Surface-Collection. Konverter im Stromschienenadapter integriert, einfach schaltbar oder stufenlos dimmbar (DALI, Casambi). Farbtemperatur 2700K, 3000K, 3500K, 4000K oder Tunable White. Binning initial  $\leq$  MacAdam 3. Farbwiedergabe CRI>80, CRI>90 oder CRI>97 für höchste Lichtqualität. Wahlweise auch CRI-Spezialausführungen für White & Colour-Fashion.

**EN** LED spotlight for 3-phase tracks. 350° rotation and 90° tilt. Recessed spherical lens for wide-angle light distribution (70°) and decorative conical reflector. Outer housing and decorative reflector available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For surface options and combinations, see Lightnet-Surface-Collection. Driver integrated into the track adapter, switchable or dimmable (DALI, Casambi). Colour temperature 2700K, 3000K, 3500K, 4000K or Tunable White. Binning  $\leq$  MacAdam 3. Colour rendering CRI>80, CRI>90 or CRI>97 for maximum light quality. Special CRI versions for white & colourfashion are also available.


**PC1 DWE - 927H-GOW**

|                    |                                                                                                                                                                                                                                                                                                                      |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Family     | <b>P:</b> Midpoint                                                                                                                                                                                                                                                                                                   |
| Type               | <b>C1:</b> Ø95mm Déco - 3-Phase Track                                                                                                                                                                                                                                                                                |
| Optical System     | <b>D:</b> Lens 70°                                                                                                                                                                                                                                                                                                   |
| Surface Finish     | <b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>F:</b> Anodic Silver, <b>U:</b> Urban Graphite, <b>D:</b> Anodic Black, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne, <b>K:</b> Satin Copper, <b>X:</b> Satin Bronze, <b>M:</b> Satin Cloud, <b>R:</b> Special Surface (please specify) |
| Control Gear       | <b>E:</b> On/Off, <b>L:</b> DALI, <b>C:</b> Casambi                                                                                                                                                                                                                                                                  |
| Colour Rendering   | <b>8:</b> CRI>80, <b>9:</b> CRI>90, <b>2:</b> CRI>97, <b>3:</b> CRI>97 (Fashion White), <b>4:</b> CRI>97 (Fashion Colour)                                                                                                                                                                                            |
| Colour Temperature | <b>27:</b> 2700K, <b>30:</b> 3000K, <b>35:</b> 3500K, <b>40:</b> 4000K, <b>TW:</b> Tunable White (only DT8)                                                                                                                                                                                                          |
| Power              | <b>M:</b> Medium Power <b>H:</b> High Power                                                                                                                                                                                                                                                                          |
| Cone Surface       | <b>W:</b> Snow White, <b>V:</b> Ivory White, <b>A:</b> Satin Silver, <b>F:</b> Anodic Silver, <b>D:</b> Anodic Black, <b>K:</b> Satin Copper, <b>G:</b> Satin Gold, <b>J:</b> Satin Pale Gold, <b>L:</b> Satin Cipria, <b>M:</b> Satin Cloud, <b>R:</b> Special Surface (please specify)                             |
| Filter             | <b>O:</b> Satin, <b>F:</b> Magic Colour                                                                                                                                                                                                                                                                              |
| Adaptor            | <b>W:</b> In-Track Electronic [white], <b>B:</b> In-Track Electronic [black]                                                                                                                                                                                                                                         |

**70° Deep Cone Lens**

| D<br>mm | Lumen/Watt<br>Medium Power | Lumen/Watt<br>High Power |
|---------|----------------------------|--------------------------|
| 95      | 2480lm/20W                 | 3480lm/29W               |

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.




Magic Colour Filter



**W** Snow White  
**W** Snow White



**F** Anodic Silver  
**F** Anodic Silver



**F** Anodic Silver  
**D** Anodic Black



**M** Satin Cloud  
**W** Snow White



**B** Jet Black  
**K** Satin Copper



**X** Satin Bronze  
**G** Satin Gold